



## Mod. NF

Blade jet nozzles

### Standard characteristics

**Body material:** Brass

**Connection type:** Threaded NPT M or BSP M

**Finish:** Natural

### Approvals



### Notes

In case of inquiry and/or order specify the following datas:

> Model and flow rate

### Available on Demand

> Body in stainless steel AISI 303 or AISI 316



MOD.	Ø inch	Ø mm	PORTATA l/min / FLOW RATE											ANG. DI SPRUZZO / SPRAY ANGLE			
			0.3 Bar	1 Bar	2 Bar	3 Bar	4 Bar	5 Bar	6 Bar	7 Bar	10 Bar	15 Bar	20 Bar	1.5 Bar	3 Bar	5 Bar	14 Bar
NF 1/2 95100	1/2"	6.4	12.3	23	32	39	45	50	55	60	71	88	101	93°	95°	99°	102°
NF 1/2 8070	1/2"	5.2	8.6	15.8	22	27	32	35	39	42	50	61	71	78°	80°	89°	92°
NF 1/2 80100	1/2"	6.4	12.3	23	32	39	45	50	55	60	71	88	101	75°	80°	83°	86°
NF 1/2 80150	1/2"	7.5	18.5	34	48	59	68	76	83	90	107	131	152	73°	80°	84°	86°
NF 1/2 80200	1/2"	8.7	25	45	64	78	90	101	111	119	143	175	200	74°	80°	82°	85°
NF 3/4 80400	3/4"	12.7	49	90	128	156	181	200	220	240	285	350	405	78°	80°	81°	83°
NF 1/2 65150	1/2"	7.5	18.5	34	48	59	68	76	83	90	107	131	152	59°	65°	68°	70°
NF 1/2 65200	1/2"	8.7	25	45	64	78	90	101	111	119	143	175	200	60°	65°	67°	69°
NF 3/4 65200	3/4"	8.7	25	45	64	78	90	101	111	119	143	175	200	60°	65°	67°	69°
NF 1/2 5015	1/2"	2.4	1.9	3.4	4.8	5.9	6.8	7.6	8.3	9	10.7	13.1	15.2	43°	50°	55°	59°
NF 1/2 50150	1/2"	7.5	18.5	34	48	59	68	76	83	90	107	131	152	45°	50°	51°	55°
NF 1/2 50200	1/2"	8.7	25	45	64	78	90	101	111	119	143	175	200	46°	50°	52°	55°
NF 3/4 50400	3/4"	12.7	49	90	128	156	181	200	220	240	285	350	405	46°	50°	52°	55°
NF 150500	1"	13.1	62	113	160	195	225	250	275	300	355	435	510	49°	50°	51°	54°
NF 150580	1"	13.9	72	131	185	225	260	290	320	345	415	510	590	49°	50°	51°	53°
NF 1/4 4015	1/4"	2.4	1.9	3.4	4.8	5.9	6.8	7.6	8.3	9.0	10.7	13.1	15.2	32°	40°	45°	48°
NF 1/4 4050	1/4"	4.4	6.2	11.3	16	19.5	23	25	28	30	36	44	51	33°	40°	43°	46°
NF 1/4 4060	1/4"	4.8	7.4	13.5	19.2	23	27	30	33	36	43	53	61	33°	40°	43°	46°
NF 1/2 40100	1/2"	6.4	12.3	23	32	39	45	50	55	60	71	88	101	34°	40°	43°	46°
NF 1/2 40150	1/2"	7.5	18.5	34	48	59	68	76	83	90	107	131	152	35°	40°	43°	44°
NF 1/2 40200	1/2"	8.7	25	45	64	78	90	101	111	119	143	175	200	36°	40°	42°	44°
NF 1/2 25100	1/2"	6.4	12.3	23	32	39	45	50	55	60	71	88	101	23°	25°	28°	32°
NF 1/2 25150	1/2"	7.5	18.5	34	48	59	68	76	83	90	107	131	152	24°	25°	28°	30°
NF 1/2 25200	1/2"	8.7	25	45	64	78	90	101	111	119	143	175	200	24°	25°	26°	29°
NF 125500	1"	13.1	62	113	160	195	225	250	275	300	355	435	510	24°	25°	26°	29°
NF 125500	1/2"	7.5	18.5	34	48	59	68	76	83	90	107	131	152	14°	15°	17°	18°
NF 1/2 15200	1/2"	8.7	25	45	64	78	90	101	111	119	143	175	200	14°	15°	17°	18°
NF 3/4 15250	3/4"	9.5	31	56	80	98	113	126	138	149	179	220	250	14°	15°	16°	17°

[www.fasspa.net](http://www.fasspa.net)



# Mod. NF

Blade jet nozzles

## Layout & Overall Dimension

