

Mod. SA

Hollow cone spray nozzles

Standard characteristics

Body material: Brass

Connection type: Threaded NPT M or BSP M

Finish: Natural

Approvals



Notes

In case of inquiry and/or order specify the following datas:

> Model, connection type, material

Available on Demand

> Body in stainless steel AISI 303 or AISI 316



MODELLO MODEL	Ø"A" inch	PORTATA – FLOW RATE L/min								
		1 BAR	1.5 BAR	2 BAR	3 BAR	4 BAR	5 BAR	6 BAR	7 BAR	10 BAR
SA 212	1/2"	95	116	134	164	190	214	236	255	290
SA 210	1/2"	64	78	88	110	126	139	152	165	200
SA 29	1/2"	52	64	74	91	105	117	129	140	165
SA 28	1/2"	41	50	57	70	81	92	103	112	130
SA 27	1/2"	31	38	44	55	63	72	77	84	91
SA 26.5	1/2"	27	33	38	47	54	61	66	72	86
SA 26	1/2"	23	28	32	39	45	50	55	60	71
Sa 25.5	1/2"	18	22	25	30	36	40	44	48	57
Sa 25	1/2"	15.8	19.3	22	27	32.3	35	39	42	50
Sa 24.5	1/2"	11.5	14	16.2	19.8	23	25	28	30	36
Sa 24	1/2"	9	11.1	12.8	15.6	18.1	20	22	24	29
Sa 23.5	1/2"	6.7	8.2	9.5	11.5	13.3	14.9	16.4	17.6	20.5
Sa 23	1/2"	4.8	5.8	6.7	8.1	9.6	10.3	11.3	12.2	14.5

Mod. SA

Hollow cone spray nozzles

Layout & Overall Dimension

