



Mod. GNA

Self induction water/foam nozzle

Standard characteristics

Nominal flow rate: From 1000 to 1500 lpm calculated at 7 barg

Body material: Stainless steel and bronze

Actuation: Manual

Jet Type: Fog, Full (Jet)

Snuction percentage: Fixed

Horizontal throw and covering angle: See diagram on next page


Base flange made in carbon steel: External diameter Ø160 mm

Reinforced PVC Pick-up pipe

Coating: Epoxy Primer + Polyurethane red coat RAL3000,
Total DFT >120 µm

Weight: ~6 Kg

Approvals



Notes

In case of inquiry and/or order specify the following data:

- > Working pressure
- > Mixing percentage

Compatible monitors

- > MB3, MB4, DOC, MKW, MKDB, MKL, MKP

Available on Demand

- > Base Flange: Other Material
- > Other Inlet connection with adapter (NH, Ghost, Storz)
- > Regolable mixing percentage
- > Coating: Other painting cycles

www.fasspa.net

Mod. GNA

Self induction water/foam nozzle

Layout & Overall Dimension






Grafico di gittata - Horizontal throw diagram

Bocchello - Nozzle GNA

Gittate a getto nebulizzato - Fog jet horizontal throw

Elevazione bocchello - Nozzle elevation 20° ÷ 30°





Grafico di gittata - Horizontal throw diagram

Bocchello - Nozzle GNA

Gittate a getto pieno - Full jet horizontal throw

Elevazione bocchello - Nozzle elevation 20° ÷ 30°



Test in still air, throw length dependent on flow rate and pressure at the nozzle

www.fasspa.net